
Aperçu

informations sur le produit



DS1.5-TW-11040000077

Push-in Din-Rail TB, connector method: Push-in connector, Rated voltage : 500 V,Rated current : 17.5 A, Number of connectors: 3, Number of potentials: 1, Cross section: 0.14 mm² - 1.5 mm², AWG: 26 - 14, Width: 3.5 mm, Color: gray, Mounting type: NS35/7.5, NS35/15

Les avantages des produits

☑Push-in connection technology, tool-free operation, more convenient and faster;
☑With orange wire button, one word or cross screwdriver can release wire.
☑Equipped with dual-channel bridge wells, circuit connection testing is more flexible.
☑Unique plug-in bridge, high circuit connection efficiency.
☑Optional marker to avoid wire mis-inserting.
☑Equipped with test holes for easy testing of the circuit.

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

Wiring data

Strip length	8~10mm
Conductor cross section solid	0.14~1.5mm²
Conductor cross section flexible	0.14~1.5 mm²
Conductor cross section solid AWG	26~14

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）

Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	500V
Rated current (III / 3)	17.5A
Rated surge voltage	6KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	32.1mm
End plate width	1.5mm
NS 35/15 Height	39.6mm
length	54mm
width	3.5mm

Overview

Connection type	In line connection
Number of rows	1
number of connections	3
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Accessoires

Marker

Top marker	ZB3.5 / ZS3.5

Side marker	ZSF3.5
Marker support	DTH3.5-25x3.5 / DTH3.5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.4x2.5
Bridge	DFBXX-3.5
End cover	D-DS1.5-TW

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Caractéristiques commerciales

Numéro de la commande	11040000077
Unité d'emballage	100
Quantité minimale de commande	100
Le poid de produit (sans emballage)	4.043