Overview

Product information



DGH95-10090000015

Through-wall terminal blocks,Rated current:232A.Rated voltage（III/3）:1000V,Width:25.0mm,Color:gray,Contact surface :Tin

Product advantages

☑ Screw connection technology,safe and reliable
☑ Through-wall installation, free positioning

Product certification

Technical data

Product drawing

3D model

Connection capacity

Conductor cross section solid	25~95mm²
Conductor cross section flexible	25~95mm²
AWG	4~4/0AWG
Strip length	27mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	230A
Rated current (D)	5A

Rated current (C)	230A

Electrical parameters IEC

Rated voltage(III/3)	1000V
Rated current	
	232A
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Hexagon screwdriver
screw thread	M8
Pitch	25mm
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10090000015
Packing unit	10
Minimum order quantity	30
Products weight (without packaging)	293