Overview

Product information



DGBSC-PG01M/4-10080000738

Feed Through Temminal Blocks,Rated current:32A,Contact surface:Tin,Connection method:PUSH-IN connection

Product advantages

- ☑ Push-In, spring connection more vibration resistance
- ☑ Special structure coding, wiring guide identification
- ☑ With a fixed buckle, the connection is more secure and stable
- ☑ IP20 High protection level

Product certification

CE

Technical data

Product drawing

3D model

Wiring data

Strip length	10~11mm

UL Electrical parameters

Rated voltage (Use Group B)	600V
Rated current (Use Group B)	20A

Connection capacity

Conductor cross section solid	0.5~4mm²
Conductor cross section flexible	0.5~4.0mm²
AWG	20~12AWG

Electrical parameters IEC

Rated voltage(III/3)	250V
Rated current	32A
Rated voltage(III/2)	400V

Item properties

Connection method	Push-in spring connection
Pitch	9.75mm
Number of potentials	5
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Business data

Order number	10080000738
Packing unit	30
Minimum order quantity	
Products weight (without packaging)	32.220