## Overview

### Product information



# 2EDGB-7.62-10020000539

Pluggable terminal blocks,Rated current:20A.Rated voltage（III/2）:400V,pitch:7.62mm,Color:green,Contact surface :Tin

### Product advantages

☑ PCB welding, plug direction is perpendicular to the PCB
☑ Multiple contacts to provide touch protection for connection

### Product certification

## Technical data

### Product drawing

### 3D model

### Dimension

| | |
|---|---|
| lettering field size | 11X10.8mm |

### Processing notes

| | |
|---|---|
| Process | Wave soldering/manual soldering |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 15A |
| Rated current (D) | 15A |

### Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 630V |
| Rated voltage(III/3) | 500V |
| Rated current | 20A |
| Rated voltage(III/2) | 630V |
| Rated voltage(II/2) | 1000V |
| Rated surge voltage(III/3) | 6KV |
| Rated surge voltage(III/2) | 6KV |
| Rated surge voltage(II/2) | 6KV |

Item properties

| | |
|---|---|
| Connection direction | 90° |
| Type of installation | PCB welding |
| Pin arrangement | Double-row in a straight line |
| Pitch | 7.62mm |
| Number of potentials | 2 |
| Pluggable or not | Yes |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃(depending on derating curve) |

## Accessories

### Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

### Tool

| | |
|---|---|
| Operating tool | / |
| Screwdriver | / |

## Business data

| | |
|---|---|
| Order number | 10020000539 |
| Packing unit | 1290 |
| Minimum order quantity | 30 |
| Products weight (without packaging) | 1.856 |