## Aperçu

### informations sur le produit



# TSF2.5-10070000095

Transformer terminal blocks,Rated current:6.3A.Rated voltage （III/2）:250V,Color:Orange ,Contact surface :Tin

### Les avantages des produits

☑ Screw connection technology,safe and reliable
☑ Rail installation method,suitable for transformer wiring

### Les certificates des produits

## Caractéristiques techniques

### Dessin de produit

### Modèle 3D

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.5~2.5mm² |
| Conductor cross section flexible | 0.5~2.5mm² |
| AWG | 20~14AWG |
| Torque | 0.8N.m |
| Strip length | 10mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 250V |
| Rated voltage (C) | 250V |
| Rated voltage (D) | 250V |

| | |
|---|---|
| Rated current (B) | 6.3A |
| Rated current (D) | 10A |
| Rated current (C) | 6.3A |

Electrical parameters IEC

| | |
|---|---|
| Rated current | |
| | 6.3A |
| Rated voltage(III/2) | 250V |
| Rated surge voltage(III/2) | 2KV |

Item properties

| | |
|---|---|
| Type of installation | panel |
| Connection method | Screw connection |
| Screwdriver | slotted-phillips screwdriver |
| screw thread | M3.5 |
| Number of potentials | 1 |
| Pluggable or not | no |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact point metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | UL1059/IEC60998 |

### Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## Accessoires

### Accessories

| | |
|---|---|
| Coding strip | TSZB4 |
| Bridge | / |
| Marking strip | / |
| Others | / |

### Tool

| | |
|---|---|
| Operating tool | / |
| Screwdriver | / |

## Caractéristiques commerciales

| | |
|---|---|
| Numéro de la commande | 10070000095 |
| Unité d'emballage | 250 |
| Quantité minimale de commande | 30 |
| Le poid de produit (sans emballage) | 9 |