Aperçu

informations sur le produit



DG12HSWP-1.2-10080000044

Feed through terminal blocks,Rated current:41A.Rated voltage（III/2）:750V,pitch:11.5mm,Color:natural,Contact surface :Zn

Les avantages des produits

☑ Can realize horizontal wire-to-wire connection
☑ Panel mounting, suitable for various situations

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

Connection capacity

Conductor cross section solid	0.75~6mm²
Conductor cross section flexible	0.75~6.0mm²
AWG	14~10AWG
Torque	0.8N.m
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A

Rated current (D)	10A

Electrical parameters IEC

Rated current	
	41A
Rated voltage(III/2)	750V
Rated power frequency voltage(1min)	3KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3.5
Pitch	11.5mm
Number of potentials	12
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	steel
Contact point metal surface	Galvanized
Insulation Materials	PA66
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessoires

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Caractéristiques commerciales

Numéro de la commande	10080000044
Unité d'emballage	65
Quantité minimale de commande	30
Le poid de produit (sans emballage)	53.8