
Aperçu

informations sur le produit



DC10-TW-PE-11020000207

Screw type Din-Rail TB， connector method: Screw/plug-in connector， Number of connectors: 3， Number of potentials: 1， Cross section: 0.5 mm² - 10 mm²， AWG: 20 - 6， Width: 10.2 mm， Color: green-yellow， Mounting type: NS 35/7.5， NS 35/15

Les avantages des produits

☑Steel screw connection technology, reliable connection；
☑Grounding structure, protection circuit；
☑The box has a baffle to prevent mis-insertion；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

Les certificates des produits

CE

Caractéristiques techniques

Dessin de produit

Modèle 3D

Wiring data

Screw type	Slotted screw
Strip length	10~12mm
Conductor cross section solid	0.5~10mm²
Conductor cross section flexible	0.5~10mm²
Conductor cross section solid AWG	20~6
screw thread	M4
Tightening torque	1.54N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	57mm
End plate width	1.5mm
NS 35/15 Height	64.5mm
length	58.7mm
width	10.2mm
Height	55.5mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	3
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Accessoires

Marker

Top marker	/

Side marker	ZB10
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×4
Bridge	DFA10
End cover	D-DC10-TW
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Caractéristiques commerciales

Numéro de la commande	11020000207
Unité d'emballage	50
Quantité minimale de commande	50
Le poid de produit (sans emballage)	32.7