
Aperçu

informations sur le produit



DCTK6-20A(H)-11020000234

Screw type Din-Rail TB， connector method: Screw/plug-in connector， Rated voltage: 630 V，Rated current: 41 A， Number of connectors: 2， Number of potentials: 1， Cross section: 0.5 mm² - 6 mm²， AWG: 22 - 8， Width: 8 mm，Color: gray， Mounting type: NS 35/7.5， NS 35/15

Les avantages des produits

☑Current terminal；
☑Steel screw connection technology, reliable connection；
☑The sliding block breaks, which can realize the circuit breaking function；
☑The box has a baffle to prevent mis-insertion；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

Les certificates des produits

CE

Caractéristiques techniques

Dessin de produit

Modèle 3D

Wiring data

Screw type	Slotted screw
Strip length	10~11mm
Conductor cross section solid	0.5~6mm²
Conductor cross section flexible	0.5~6mm²
Conductor cross section solid AWG	22~8
screw thread	M4
Tightening torque	1.2N.m

Environmental conditions	
Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

UL Electrical parameters	
Rated current	45A

IEC Electrical parameters	
Rated voltage (III / 3)	630V
Rated current (III / 3)	41A
Rated surge voltage	8KV

Environmental protection	
REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension	
NS 35/7,5 Height	46.55mm
End plate width	1.5mm
NS 35/15 Height	54.05mm
length	70.9mm
width	8mm
Height	46.1mm

Overview	
Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA

Flame retardant grade, in line with UL 94	V0

Accessoires

Marker

Top marker	/
Side marker	ZB8
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×4
Bridge	FBRI6-RTK/S-XXP
End cover	D-DCTK6
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Caractéristiques commerciales

Numéro de la commande	11020000234
Unité d'emballage	50
Quantité minimale de commande	50
Le poid de produit (sans emballage)	20.967