
Aperçu

informations sur le produit



DC95-11020000213

Screw type Din-Rail TB， connector method: Screw/plug-in connector， Rated voltage: 1000 V，Rated current: 232 A， Number of connectors: 2， Number of potentials: 1， Cross section: 25 mm² - 95 mm²， AWG: 2 - 4/0， Width: 25 mm， Color: gray， Mounting type: NS 35/7.5， NS 35/15

Les avantages des produits

☑Steel screw connection technology, reliable connection；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

Les certificates des produits

CE

Caractéristiques techniques

Dessin de produit

Modèle 3D

Wiring data

Screw type	Allen screws
2 flexible conductors with a TWIN ferrule	25-35mm²
Conductor cross section flexible (ferrule with plastic sleeve)	25-95mm²
Conductor cross section flexible (ferrule without plastic sleeve)	25-95mm²
Strip length	33~35mm
Conductor cross section solid	25~95mm²
Conductor cross section flexible	25~95mm²
Conductor cross section solid AWG	2~4/0

screw thread	M8
Tightening torque	20N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

UL Electrical parameters

Rated current	230A

IEC Electrical parameters

Rated voltage (III / 3)	1000V
Rated current (III / 3)	232A
Rated surge voltage	8KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	90mm
NS 35/15 Height	97.5mm
length	83mm
width	25mm
Height	90mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	no

Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Accessoires

Marker

Top marker	/
Side marker	ZT12
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	/
Bridge	/
End cover	/
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Caractéristiques commerciales

Numéro de la commande	11020000213
Unité d'emballage	20
Quantité minimale de commande	20
Le poid de produit (sans emballage)	199.35