
Aperçu

informations sur le produit



DCKKB4-02A(H)-11020000191

Screw type Din-Rail TB， connector method: Screw/plug-in connector， Rated voltage: 800 V， Rated current: 32 A， Number of connectors: 4， Number of potentials: 1， Cross section: 0.5 mm² - 4mm²， AWG: 22 - 10， Width: 6.1 mm， Color: gray， Mounting type: NS 35/7.5， NS 35/15

Les avantages des produits

☑Steel screw connection technology, reliable connection；
☑Equipped with dual-channel bridge wells, circuit connection testing is more flexible；
☑Unique plug-in bridge, high circuit connection efficiency；
☑The box has a baffle to prevent mis-insertion；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

Les certificates des produits

CE

Caractéristiques techniques

Dessin de produit

Modèle 3D

Wiring data

Screw type	Cross & Slotted screw
2 flexible conductors with a TWIN ferrule	0.5-1.5mm²
Conductor cross section flexible (ferrule with plastic sleeve)	0.5-2.5mm²
Conductor cross section flexible (ferrule without plastic sleeve)	0.5-4mm²
Strip length	8~9mm
Conductor cross section solid	0.5~6mm²

Conductor cross section flexible	0.5~4mm²
Conductor cross section solid AWG	22~10
screw thread	M3
Tightening torque	0.6N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	800V
Rated current (III / 3)	32A
Rated surge voltage	8KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	63mm
End plate width	1.5mm
NS 35/15 Height	70.5mm
length	76mm
width	6.1mm
Height	61.8mm

Overview

Connection method	screw connection
Number of rows	2
number of connections	4

Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Accessoires

Marker

Top marker	/
Side marker	ZB6
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.6×3.5
Bridge	DFA4
End cover	D-DCKKB2.5
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Caractéristiques commerciales

Numéro de la commande	11020000191
Unité d'emballage	50
Quantité minimale de commande	50
Le poid de produit (sans emballage)	17.5