Aperçu

informations sur le produit



DC4-HE-LD24-11020000120

Screw type Din-Rail TB， connector method: Screw/plug-in connector， Rated voltage: 24 V， Rated current: 6.3 A， Number of connectors: 2， Number of potentials: 1， Cross section: 0.5 mm² - 4mm²， AWG: 22 - 10， Width: 8 mm， Fuse type: Glass/ceramic/...， Fuse type: G / 5 x 20， Color: black， Suitable for 24 V DC LED, Mounting type: NS 35/7.5， NS 35/15.

Les avantages des produits

☑Fuse terminal blocks；
☑Steel screw connection technology, reliable connection；
☑The box has a baffle to prevent mis-insertion；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

Les certificates des produits

CE

Caractéristiques techniques

Dessin de produit

Modèle 3D

Wiring data

Screw type	Slotted screw
2 flexible conductors with a TWIN ferrule	0.5-1.5mm²
Conductor cross section flexible (ferrule with plastic sleeve)	0.5-2.5mm²
Conductor cross section flexible (ferrule without plastic sleeve)	0.5-4mm²
Strip length	8~9mm
Conductor cross section solid	0.5~6mm²

Conductor cross section flexible	0.5~4mm²
Conductor cross section solid AWG	22~10
screw thread	M3
Tightening torque	0.6N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated current (Ill / 3)	6.3A
Rated surge voltage	6KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	48mm
End plate width	1.5mm
NS 35/15 Height	55.5mm
length	58mm
width	8mm
Height	46.5mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	Yes

Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
fuse	G/5 x 20
Fuse type	Glass/ceramic/...

Accessoires

Marker

Top marker	/
Side marker	ZB8
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.6×3.5
Bridge	EBC2-8 / EBC3-8 / EBC10-8
End cover	D-DC4-HE
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Caractéristiques commerciales

Numéro de la commande	11020000120
Unité d'emballage	50
Quantité minimale de commande	50

Le poid de produit (sans emballage)	12.36