Aperçu

informations sur le produit



DCKKB10-11020000183

Screw type Din-Rail TB， connector method: Screw/plug-in connector， Rated voltage: 500 V，Rated current: 57 A， Number of connectors: 4， Number of potentials: 1， Cross section: 0.5 mm² - 10 mm²， AWG: 20 - 6， Width: 10 mm， Color: gray， Mounting type: NS 35/7.5， NS 35/15

Les avantages des produits

☑Steel screw connection technology, reliable connection；
☑Equipped with dual-channel bridge wells, circuit connection testing is more flexible；
☑Unique plug-in bridge, high circuit connection efficiency；
☑The box has a baffle to prevent mis-insertion；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

Les certificates des produits

CE

Caractéristiques techniques

Dessin de produit

Modèle 3D

Wiring data

Screw type	Slotted screw
Strip length	10~12mm
Conductor cross section solid	0.5~10mm²
Conductor cross section flexible	0.5~10mm²
Conductor cross section solid AWG	20~6
screw thread	M4
Tightening torque	1.54N.m

Environmental conditions	
Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

UL Electrical parameters	
Rated current	65A

IEC Electrical parameters	
Rated voltage (III / 3)	500V
Rated current (III / 3)	57A
Rated surge voltage	6KV

Environmental protection	
REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension	
NS 35/7,5 Height	72.5mm
End plate width	1.5mm
NS 35/15 Height	80mm
length	83.9mm
width	10mm
Height	71.2mm

Overview	
Connection method	screw connection
Number of rows	2
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA

Flame retardant grade, in line with UL 94	V0

Accessoires

Marker

Top marker	/
Side marker	ZB10
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×4
Bridge	DFA10
End cover	D-DCKKB10
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Caractéristiques commerciales

Numéro de la commande	11020000183
Unité d'emballage	20
Quantité minimale de commande	20
Le poid de produit (sans emballage)	39.45