
## Aperçu

### informations sur le produit



# DMK-003-F(6-10mm²)-21020000268

Heavy-duty insert,Number of contacts:3,Dimension:1 module Spaces,Rated voltage :690V,Rated current:40A,Female insert,axial Screw connector

### Les avantages des produits

☑Axial Screw connection technology, applicable to a wide range of wire specifications;
☑Less materials, easy to manage;
☑Modular products, easy to assemble and maintain 。

### Les certificates des produits

CE

## Caractéristiques techniques

### Dessin de produit

### Modèle 3D

### Marking

| | |
|---|---|
| classification | Insert |
| Series | DM |

### versions

| | |
|---|---|
| Connection method | Axial screw connection |
| Female/Male | Female |
| Dimension | 1 module |
| Number of positions | 3 |
| PE Contacts | No |

### Material characteristics

| | |
|---|---|
| Material（insert） | Polycarbonate（PC） |
| Materia（Contact） | Copper alloy |
| Surface（Contact） | Silver plated |
| Flammability rating | V-0 |
| color | Grey/White（RAL 7032） |
| RoHS | Comply with RoHS exemptions |

Electrical parameters

| | |
|---|---|
| Rated current | 40A |
| | 690V |
| Rated pulse voltage | 8KV |
| Pollution level | 3 |
| On the basis of UL /CSARated current | 600V |
| Insulation resistance | ≥10000MΩ |
| Contact resistance | ≤0.3mΩ |
| Temperature range | -40℃~+125℃ |
| working life-mating cycles | ≥500 time |
| Strip length | 5-11mm |
| Rated torque | 1.5N.m(2.5/4mm²) 2N.m(6/10mm²) |
| Conductor cross sections（mm²） | 6-10mm² |
| Conductor cross sections(AWG) | 10-8AWG |

Standards

| | |
|---|---|
| Connection meets standards | DIN EN 60664 DIN EN 61984 |

Accessoires

Accessories

| | |
|---|---|
| Screwdriver | / |

## Caractéristiques commerciales

| | |
|---|---|
| Numéro de la commande | 21020000268 |
| Unité d'emballage | 100 |
| Quantité minimale de commande | 5 |
| Le poid de produit (sans emballage) | 30.12 |