Aperçu

informations sur le produit



DG220B-2.1-10060002741

PCB spring terminal blocks,Rated current:6A.Rated voltage（III/2）:320V,pitch:2.1mm,Color:gray,Contact surface :Tin

Les avantages des produits

- ☑ PUSH-IN connection technology, fast wiring
- ☑ Suitable for single wire
- ☑ Wire Connector for Mini Junction Box

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

Connection capacity

Conductor cross section solid	0.5~1.0mm²
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	150V
Rated voltage (D)	150V
Rated current (B)	7A
Rated current (D)	7A

Electrical parameters IEC

Rated voltage	320V
Rated voltage(III/3)	250V
Rated current	6A
Rated voltage(III/2)	320V
Rated voltage(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	0°
Connection method	Push-in spring connection
Pitch	2.1mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessoires

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	DG220J

Tool

Operating tool	/
Screwdriver	/

Caractéristiques commerciales

Numéro de la commande	10060002741
Unité d'emballage	1250
Quantité minimale de commande	30
Le poid de produit (sans emballage)	0.413