## Aperçu

### informations sur le produit



# DG263-10.0-10060002758

PCB spring terminal blocks,Rated current:41A.Rated voltage （III/2）:1000V,pitch:10.0mm,Color:gray,Contact surface :Tin

### Les avantages des produits

☑ Universal installation method, suitable for various situations
☑ 45°connection can realize multi-row layout on PCB
☑ Different poles can be combined through the side lock

### Les certificates des produits

## Caractéristiques techniques

### Dessin de produit

### Modèle 3D

### Processing notes

| | |
|---|---|
| Process | Wave soldering/manual soldering |

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.2~6mm² |
| Conductor cross section flexible | 0.2~6.0mm² |
| AWG | 24~10AWG |
| Strip length | 12mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated current (B) | 30A |

## Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 1000V |
| Rated voltage(III/3) | 630V |
| Rated current | 41A |
| Rated voltage(III/2) | 1000V |
| Rated voltage(II/2) | 1000V |
| Rated surge voltage(III/3) | 8KV |
| Rated surge voltage(III/2) | 8KV |
| Rated surge voltage(II/2) | 8KV |

## Item properties

| | |
|---|---|
| Connection direction | 45° |
| Type of installation | PCB welding |
| Pin arrangement | Double-row in a straight line |
| Connection method | spring-cage connection |
| Pitch | 10mm |
| Number of potentials | 1 |
| Pluggable or not | no |
| Number of rows | 1 |

## Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact point metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |

| | |
|---|---|
| Flammability rating | UL94V-0 |

### Mechanical tests

| | |
|---|---|
| Test Specification | IEC60947/UL1059 |

### Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## Accessoires

### Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

### Tool

| | |
|---|---|
| Operating tool | / |
| Screwdriver | / |

## Caractéristiques commerciales

| | |
|---|---|
| Numéro de la commande | 10060002758 |
| Unité d'emballage | 100 |
| Quantité minimale de commande | 30 |
| Le poid de produit (sans emballage) | 5.894 |