Aperçu

informations sur le produit



DG127H-5.08-10040002252

PCB terminal blocks,Rated current: 15A,Rated voltage （III/2）250V,Cross section:0.2-1.5mm²,pitch:5.08mm,connector method:Screw connector with tension sleeve,Color:green,Contact surface :Tin

Les avantages des produits

☑ Fixed screw connection technology,safe and reliable
☑ Different poles can be combined through the side lock
☑ Universal installation method to ensure a high degree of flexibility in device design

Les certificates des produits

VDE

Caractéristiques techniques

Dessin de produit

Modèle 3D

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

Conductor cross section solid	0.2~1.5mm²
Conductor cross section flexible	0.2~1.5mm²
AWG	26~14AWG
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	12A

Electrical parameters IEC

Rated voltage	250V
Rated current	15A
Rated voltage(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5.08mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests	
Test Specification	UL1059/IEC60998

Environmental data	
Ambient temperature (operation)	-40℃~105℃

Accessoires

Accessories	
Coding strip	/
Bridge	DG019-5.0
Marking strip	/
Others	/

Tool	
Operating tool	/
Screwdriver	0.6x3.5mm，Slotted screwdriver

Caractéristiques commerciales

Numéro de la commande	10040002252
Unité d'emballage	200
Quantité minimale de commande	30
Le poid de produit (sans emballage)	2.65