Aperçu

informations sur le produit



DG129-5.08-10040006692

Fixed terminal block, nominal working current: 20A, rated voltage (III/2) 250V, rated cross-section: 0.5-2.5mm², pitch: 5.08mm, connection method: screw connection with crimping frame, color: green, Contact Surface: Tin

Les avantages des produits

☑ Universal installation, ensuring a high degree of flexibility in device design
☑ Different digits can be combined through the lock on the side

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

Conductor cross section solid	0.5~2.5mm²
Conductor cross section flexible	0.5~2.5mm²
AWG	26~12AWG
Torque	0.5N.m
Strip length	8mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	250V
Rated current	20A
Rated voltage(III/2)	250V
Rated power frequency voltage(1min)	2KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5.08mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66

Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessoires

Tool

screwdriver	0.6x3.5mm, slotted screwdriver
Wire take tool	/

Accessories

coding strip	/
bridge	/
marker strip	/
other	/

Caractéristiques commerciales

Numéro de la commande	10040006692
Unité d'emballage	200
Quantité minimale de commande	
Le poid de produit (sans emballage)	4.04