Overview

Product information



DSW-A5K0005-30090000001

5 10/100Mbs BaseT port, IP30,Operating temperature-40°C~+75°C.12/24/48 VDC & 24VAC (9.6~60 VDC & 18~30 VAC) power supply enter(Only connect to class 2 power).

Product advantages

☑Unmanaged Industrial Switch made from Anti-Corrosion Aluminum Alloy.
☑5 10/100BaseT Ports.
☑12/24/48 VDC & 24VAC (9.6~60VDC & 18~30 VAC) Power Input
☑Operating Temperature from -40°C to +75°C.
☑IP30 Protection Class

Product certification

Technical data

Product drawing

3D model

Interface

Port 1 Type	RJ45
Number of ports 1	5
Transmission rate	10/100 Mbps

Mechanical structure

Shell material	Die-cast aluminum alloy housing
switch	QoS function, BSP (Broadcast Storm Protection) function
Installation method	Card rail installation
Protection class	IP30

Exchange property	
MAC table size	4K
Bandwidth backplane	16Gbps
packet buffer	1.5Mb
MTBF	
Standards compliant	Telcordia SR-332
operating hours	≥38,7641H
Warranty	
Warranty	5 years
Power supply	
Supply voltage range	9.6~60VDC & 18~30VAC
Reverse voltage protection	support
Connection Type	2P plug-in terminal
Connecting wire diameter	0.5~1.5mm/ 28~16AWG
Overcurrent protection	support
Input voltage	12/24/48 VDC & 24 VAC
Environmental data	
working altitude	≤2000m
Operating temperature	-40°C~+75°C
storage temperature	-40°C~+85°C
humidity	5% ~ 95% (non-condensing)
Dimension	
high	100mm
length	61.8mm
width	24mm

Accessories

Business data

Order number	30090000001
Packing unit	1 STK
Minimum order quantity	1 STK
Products weight (without packaging)	170g