
Overview

Product information



DGBSC-PG03M/4-03P-10080000516

Feed Through Temminal Blocks,Rated current:25A,Contact surface:Tin,Connection method:Push-in spring connection

Product advantages

☑ Push-In, spring connection more vibration resistance
☑ Special structure coding, wiring guide identification
☑ 1 pole 2 holes, to achieve circuit shunt

Product certification

CE

Technical data

Product drawing

3D model

Electrical parameters UL

Rated current (B)	23A

Packaging information

Type of packaging	box-packed

Connection capacity

Conductor cross section flexible, with ferrule without plastic sleeve	0.5-4mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve	0.5-2.5mm²
Conductor cross section flexible， with TWIN ferrule with plastic sleeve	/

Conductor cross section solid	0.5~4mm²
AWG	20~12AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	600V

Electrical parameters IEC

Rated voltage	250V
Rated voltage(III/3)	250V
Rated current	25A
Rated surge voltage(III/3)	4KV

Item properties

Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	3
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Shell color	Black
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984

Environmental data	
Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Business data

Order number	10080000516
Packing unit	100
Minimum order quantity	
Products weight (without packaging)	9.65