Aperçu

informations sur le produit



TSC10-10070000039

Transformer terminal blocks,Rated current:57A.Rated voltage （III/2）:1000V,Color:Orange ,Contact surface :Tin

Les avantages des produits

☑ Screw connection technology,safe and reliable
☑ Rail installation method,suitable for transformer wiring

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

Connection capacity

Conductor cross section solid	0.2~10mm²
Conductor cross section flexible	0.2~10mm²
AWG	24~6AWG
Torque	1.2N.m
Strip length	11mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V

Rated current (B)	65A
Rated current (D)	5A
Rated current (C)	65A

Electrical parameters IEC

Rated current	
	57A
Rated voltage(III/2)	1000V
Rated power frequency voltage(1min)	3.5KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Pitch	11.25mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessoires

Accessories

Coding strip	TZB4
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Caractéristiques commerciales

Numéro de la commande	10070000039
Unité d'emballage	150
Quantité minimale de commande	30
Le poid de produit (sans emballage)	34.16