
## Aperçu

### informations sur le produit



# DC2.5-QU-11020000214

Screw type Din-Rail TB， connector method: Screw/plug-in connector， Rated voltage: 500 V，Rated current: 24 A， Number of connectors: 4， Number of potentials: 1， Cross section: 0.2 mm² - 4 mm²， AWG: 28 - 12， Width: 5.1 mm， Color: gray， Mounting type: NS 35/7.5， NS 35/15

### Les avantages des produits

☑Steel screw connection technology, reliable connection；
☑Equipped with dual-channel bridge wells, circuit connection testing is more flexible；
☑Unique plug-in bridge, high circuit connection efficiency；
☑The box has a baffle to prevent mis-insertion；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

### Les certificates des produits

CE

## Caractéristiques techniques

### Dessin de produit

### Modèle 3D

### Wiring data

| | |
|---|---|
| Screw type | Cross & Slotted screw |
| Conductor cross section flexible (ferrule with plastic sleeve) | 0.5-1.5mm² |
| Strip length | 8~9mm |
| Conductor cross section solid | 0.2~4mm² |
| Conductor cross section flexible | 0.2~2.5mm² |
| Conductor cross section solid AWG | 28~12 |
| screw thread | M2.5 |

| | |
|---|---|
| Tightening torque | 0.4N.m |

| Environmental conditions | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |

| IEC Electrical parameters | |
|---|---|
| Rated voltage (III / 3) | 500V |
| Rated current (III / 3) | 24A |
| Rated surge voltage | 6KV |

| Environmental protection | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

| Dimension | |
|---|---|
| NS 35/7,5 Height | 49.2mm |
| End plate width | 1.5mm |
| NS 35/15 Height | 56.7mm |
| length | 54.4mm |
| width | 5.1mm |
| Height | 47.7mm |

| Overview | |
|---|---|
| Connection method | screw connection |
| Number of rows | 1 |
| number of connections | 4 |
| Open-end side panels | Yes |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

## Accessoires

### Marker

| | |
|---|---|
| Top marker | / |
| Side marker | ZB5 / WB5 |
| Marker support | / |

### Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) | 0.6×3.5 |
| Bridge | DFA2.5 |
| End cover | D-DC4-QU |
| Partition plate | / |

### Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5 & NS35/15 |

## Caractéristiques commerciales

| | |
|---|---|
| Numéro de la commande | 11020000214 |
| Unité d'emballage | 100 |
| Quantité minimale de commande | 100 |
| Le poid de produit (sans emballage) | 8.17 |