
Aperçu

informations sur le produit



D2MK-002-F(16-35mm²)-21020000256

Heavy-duty insert,Number of contacts:2,Dimension:2 module Spaces,Rated voltage :1000V,Rated current:100A,Female insert,axial Screw connector

Les avantages des produits

☑Axial Screw connection technology, applicable to a wide range of wire specifications;
☑Less materials, easy to manage;
☑Modular products, easy to assemble and maintain 。

Les certificates des produits

CE

Caractéristiques techniques

Dessin de produit

Modèle 3D

Marking

classification	Insert
Series	DM

versions

Connection method	Axial screw connection
Female/Male	Female
Dimension	2 module
Number of positions	2
PE Contacts	No

Material characteristics

Material（insert）	Polycarbonate（PC）
Materia（Contact）	Copper alloy
Surface（Contact）	Silver plated
Flammability rating	V-0
color	Grey/White（RAL 7032）
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	100A
	1000V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	13mm
Rated torque	8N.m(25/35mm²) 9N.m(50mm²) 10N.m(70mm²)
Conductor cross sections（mm²）	16-35mm²
Conductor cross sections(AWG)	6-2AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984

Accessoires

Accessories

SW 4 internal hexagonal wrench	/

Caractéristiques commerciales

Numéro de la commande	21020000256
Unité d'emballage	100
Quantité minimale de commande	5
Le poid de produit (sans emballage)	80