Aperçu

informations sur le produit



DG500A-5.0-100A-10040004395

PCB terminal blocks，Rated current：18A，Rated voltage（III/2）：250V，Cross section：1.0-2.5mm²，Pitch：5.0mm，Connection method：Screw connector with tension sleeve，Color：Green，Contact surface：Tin

Les avantages des produits

☑ Universal connection method to ensure a high degree of flexibility in device design
☑High and low integrated structure,more reliable for customers to use
☑ Multi-layer wire connection can achieve higher contact density
☑ Different poles can be combined through the side lock

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

Conductor cross section solid	1.0~2.5mm²
Conductor cross section flexible	1.0~2.5mm²
AWG	28~12AWG
Torque	0.5N.m
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	250V
Rated current	18A
Rated voltage(III/2)	250V
Rated power frequency voltage(1min)	2KV

Item properties

Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5mm
Number of potentials	4
Pluggable or not	no
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	UL1059/IEC60998
Environmental data	
Ambient temperature (operation)	-40℃~105℃

Accessoires

Caractéristiques commerciales

Numéro de la commande	10040004395
Unité d'emballage	700
Quantité minimale de commande	
Le poid de produit (sans emballage)	6.32