
Aperçu

informations sur le produit



FBUS22.5-05P-10020001619

DIN rail bus connector, Number of potentials: 5, pitch: 3.81 mm, Color: light gray, Contact surface : gold,Contact point gold plating,bus connector used to connect electronic module housing. Color: light gray.Compatible housing:FMEH-04P.

Les avantages des produits

☑Modular design
☑Multiple connection technologies optional, signal, data,and power transmission can be realized
☑bus connector is optional
☑Various personalized solutions can be achieved according to customer needs

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

Item properties

Pitch	3.81mm
Number of potentials	5
Type of installation(din rail \ panel \ PCB soldering)	din rail
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items(Compliant with REACH/RoHS)	Yes
Conductor material (copper / copper alloy)	Copper alloy
Contact point metal surface(conductor contact with wire)	gold

Contact zone metal surface(insert&pullout)	gold
Shell color	light gray
Insulation Materials (main class)	PA66
Insulating material group	I
Flammability rating	V0

Mechanical tests

Test standard (standard no.)	UL1059

Durability test

Insert / pull out cycle	50

Electrical parameters

Rated current(B) UL	7A
	150V

Environmental data

Ambient temperature (operation)	-40℃～ +105℃
Ambient temperature (storage / transport)	-40℃～ +70℃

Accessoires

Accessories

Caractéristiques commerciales

Numéro de la commande	10020001619
Unité d'emballage	60
Quantité minimale de commande	60
Le poid de produit (sans emballage)	4.58