
Panoramica

Informazioni sul prodotto



DGBSC-SG01/4-10050000465

PCB spring terminal blocks,Rated current:32A.Rated voltage （III/2）:450V,pitch:5.6mm,Color:transparent,Contact surface :Tin

Vantaggi del prodotto

☑ Rotatable operating handle,easy to operate
☑ Suitable for field wiring,saving installation time

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Connection capacity

Conductor cross section solid	0.2~4mm²
Conductor cross section flexible	0.2~4.0mm²
AWG	24~12AWG
Strip length	12mm

Electrical parameters UL

Rated voltage (B)	600V

Electrical parameters IEC

Rated current	32A

Rated voltage(III/2)	450V

Item properties

Connection method	Push-in spring connection
Pitch	5.6mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)	-40℃~85℃

Accessori

Accessories

Coding strip	/
Bridge	/
Marking strip	/

Others	/

Tool

Operating tool	/
Screwdriver	/

Dati aziendali

numero d'ordine	10050000465
Unità di imballaggio	100
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	2.22