Panoramica

Informazioni sul prodotto



DG25H-B-12020000054

Single layer PCB fence terminal,nominal current15A.Rated voltage(UL):300V,Rated cross section:22~14AWG,pitch:7.62mm,Color:black,Contact surface:Tin

Vantaggi del prodotto

☑Screw connection for worldwide use
☑Screw connection for worldwide use
☑Solder board installation, which can realize the electrical connection between the device and the PCB

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Connection capacity

AWG	22~14AWG
Torque	0.5N.m

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Item properties

Type of installation	PCB welding

Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M3
Pitch	7.62mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessori

Accessories

Dati aziendali

numero d'ordine	12020000054

Unità di imballaggio	830
Quantità di ordine minimo	/
Peso dei prodotti (senza imballaggio)	4.584