Panoramica

Informazioni sul prodotto



DG2350-12010000491

Single layer PCB fence terminal, nominal current: 120A. Rated voltage (UL): 600V, rated cross section: 2~1/0AWG, pitch: 23.5mm, color: black, contact surface: tin

Vantaggi del prodotto

☑ Screw connection for worldwide use
☑ Barrier wiring structure, stable and reliable connection
☑ It can meet the high current electrical connection at the power end

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Wiring capacity

torque	5.5N.m
Connectable conductor cross section	2~1/0AWG

Device properties

number of digits	23.5mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V

Rated current (B)	120A
Rated current (D)	5A
Rated current (C)	120A

Item properties

Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M8
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PBT
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059

Environmental data

Ambient temperature (operation)	-40℃~120℃

Accessori

Dati aziendali

numero d'ordine	12010000491
Unità di imballaggio	40
Quantità di ordine minimo	/
Peso dei prodotti (senza imballaggio)	103.64