## Panoramica

### Informazioni sul prodotto



# 5A-GM-0.33-92116900079

5A silver gold male pins,Adapter wire specification0.33mm²

### Vantaggi del prodotto

☑High-precision turning process, stable and reliable products;
☑Gold-plated and silver-plated are available, suitable for different environmental requirements;
☑Comprehensive products, resistant to temperature changes, shocks and harsh environments。

### Certificazione del prodotto

## Dati tecnici

### Disegno del prodotto

### Modello 3D

### Marking

| | |
|---|---|
| classification | Contact |
| Series | 5A |
| Contact type | Crimping contact |

### versions

| | |
|---|---|
| Female/Male | Male |
| manufacturing technique | Turning |

### Material characteristics

| | |
|---|---|
| RoHS | Comply with RoHS exemptions |
| Plating material | Gold plate |
| Material | Copper alloy |

## Standards

| | |
|---|---|
| Connection meets standards | EN 60664-1 IEC 61984 |

## Technical specification

| | |
|---|---|
| Conductor cross sections（mm²） | 0.33mm² |
| Conductor cross sections(AWG) | 22AWG |
| Working current | ≤10A |
| Contact resistance | ≤3mΩ |
| Plating Thickness | ≥3μ" |
| Temperature range | -40℃~+125℃ |
| Strip length | 8mm |
| working life-mating cycles | ≥500 |

## Accessori

## Dati aziendali

| | |
|---|---|
| numero d'ordine | 92116900079 |
| Unità di imballaggio | 100 |
| Quantità di ordine minimo | 100 |
| Peso dei prodotti (senza imballaggio) | 0.186 |