Panoramica

Informazioni sul prodotto



16A-SM-4.0-92116900085

16A silver plating male pins,Adapter wire specification4.0mm²

Vantaggi del prodotto

☑High-precision turning process, stable and reliable products;
☑Gold-plated and silver-plated are available, suitable for different environmental requirements;
☑Comprehensive products, resistant to temperature changes, shocks and harsh environments。

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Marking

classification	Contact
Series	16A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Silver plated
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984

Technical specification

Conductor cross sections（mm²）	4.0mm²
Conductor cross sections(AWG)	12AWG
Working current	≤16A
Contact resistance	≤1mΩ
Plating Thickness	≥2μm
Temperature range	-40℃~+125℃
Strip length	7.5mm
working life-mating cycles	≥500

Accessori

Dati aziendali

numero d'ordine	92116900085
Unità di imballaggio	100
Quantità di ordine minimo	100
Peso dei prodotti (senza imballaggio)	1.57