Panoramica

Informazioni sul prodotto



Relay base-DPTF08A-3-00A(H)-30020000053

DPTFrelay base,used for2PDTrelay,screw connection

Vantaggi del prodotto

☑Plug-in relay socket
☑Safe isolation between coil and contacts
☑10A, 2PDTgrade
☑Arc partition between adjacent columns

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Environmental data

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage / transport)	-40~+65℃

Technical data

Rated voltage UN	300V
Rated current IN	10A
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter

Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Dimension

length	71mm
width	30mm
Depth including bracket	27.5mm

Accessori

Dati aziendali

numero d'ordine	30020000053
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	