
Áttekintés

Termék információ



2EDGKHV-7.62-10010004798

Pluggable terminal blocks,Rated current:16A.Rated voltage （III/2）:1000V,pitch:7.62mm,Color:green,Contact surface :Tin

A termék előnyei

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying parts can be installed
☑ Universal installation method, suitable for various situations

Termék tanúsítás

Műszaki adatok

Termékrajz

3D modell

Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	30~12AWG
Torque	0.6N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated current (B)	20A

Rated current (C)	20A

Electrical parameters IEC

Rated voltage	1000V
Rated voltage(III/3)	1000V
Rated current	16A
Rated voltage(III/2)	1000V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	0°
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	7.62mm
Number of potentials	3
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66

Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

Melléklet

Tool

Screwdriver	0.6x3.5，Slotted screwdriver
Operating tool	/

Accessories

Coding strip	2EDG-PWI
Bridge	/
Marking strip	/
Others	/

Üzleti adatok

Rendelésszám	10010004798
Csomagolási egység	100
Minimális rendelési mennyiség	30
A termékek súlya (csomagolás nélkül)	6.16