
Áttekintés

Termék információ



2EDGKDM-5.08-10020000863

Pluggable terminal blocks,Rated current:20A.Rated voltage（III/2）:320V,pitch:5.08mm,Color:green,Contact surface :Tin

A termék előnyei

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying requirements can be met
☑ Universal installation method, suitable for various situations

Termék tanúsítás

Műszaki adatok

Termékrajz

3D modell

Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	26~12AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	10A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated current	20A
Rated voltage(III/2)	320V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	0°
Connection method	Push-in spring connection
Pitch	5.08mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

Melléklet

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	2EDG-PWI

Tool

Operating tool	/
Screwdriver	/

Üzleti adatok

Rendelésszám	10020000863
Csomagolási egység	150
Minimális rendelési mennyiség	30
A termékek súlya (csomagolás nélkül)	4