
Áttekintés

Termék információ



DSKK4-11040000064

Double-layer rail terminal, wiring method: direct insertion connection, rated voltage: 500 V, rated current: 32 A, connection quantity: 4, digit: 1, wiring capacity: 0.2 mm² - 6 mm², AWG: 24 - 10, width: 6.2 mm, color: gray, installation method: NS35/7.5, NS35/15

A termék előnyei

☑Double-level terminal block.
☑Push-in connection technology, tool-free operation, more convenient and faster;
☑With orange wire button, one word or cross screwdriver can release wire.
☑Unique plug-in bridge, high circuit connection efficiency.
☑Optional marker to avoid wire mis-inserting.
☑Equipped with test holes for easy testing of the circuit.

Termék tanúsítás

Műszaki adatok

Termékrajz

3D modell

Wiring data

Strip length	11~13mm
Conductor cross section solid	0.2~6mm²
Conductor cross section flexible	0.2~4mm²
Conductor cross section solid AWG	24~10

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）

Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	500V
Rated current (III / 3)	32A
Rated surge voltage	6KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	48.75mm
End plate width	2.2mm
NS 35/15 Height	56.25mm
length	83.5mm
width	6.2mm

Overview

Connection type	In line connection
Number of rows	2
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Melléklet

Marker

Top marker	/

Side marker	ZSF6
Marker support	DMTH5-2 / DMTH5-3

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5
Bridge	DFBXX-6.2
End cover	D-DSKK4

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Üzleti adatok

Rendelésszám	11040000064
Csomagolási egység	50
Minimális rendelési mennyiség	50
A termékek súlya (csomagolás nélkül)	16.41