Panoramica

Informazioni sul prodotto



10A-SM-0.37-92116900100

10A silver plating male pins,Adapter wire specification0.37mm²

Vantaggi del prodotto

☑High-precision turning process, stable and reliable products;
☑Gold-plated and silver-plated are available, suitable for different environmental requirements;
☑Comprehensive products, resistant to temperature changes, shocks and harsh environments。

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Marking

classification	Contact
Series	10A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Silver plated
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984

Technical specification

Conductor cross sections（mm²）	0.37mm²
Conductor cross sections(AWG)	22AWG
Working current	≤10A
Contact resistance	≤3mΩ
Plating Thickness	≥2μm
Temperature range	-40℃~+125℃
Strip length	8mm
working life-mating cycles	≥500

Accessori

Dati aziendali

numero d'ordine	92116900100
Unità di imballaggio	100
Quantità di ordine minimo	100
Peso dei prodotti (senza imballaggio)	0.6404