Overview

Product information



Push-in connection relay Socket-DPWF-08A-F3-00A(H)-30020000135

DPWF Relay Socket, used for 2 PDT relays, push-in connection

Product advantages

☑ Push-in relay socket
☑ Safe isolation between coils and contacts
☑ 12A maximum switching current

Product certification

Technical data

Product drawing

3D model

Dimension

width	26.8mm
length	92mm
Depth including bracket	86mm

Environmental data

Ambient temperature (operation)	-45℃～+85℃
Ambient temperature (storage / transport)	-45℃～+85℃

Technical data

Rated voltage UN	300V

Rated current IN	12A
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
Connection method	PUSH-IN connection
Stripping length	10-12mm
Cross section of flexible conductor	0.25-2.5mm²
Connectable guide cross section AWG	22-14AWG

Connection data 2

Connection name	Output
Stripping length	10-12mm
Cross section of flexible conductor	0.25-2.5mm²
Connectable guide cross section AWG	22-14AWG
Connection method	PUSH-IN connection

Accessories

Accessory

Bridge	DFB2-27-13-00Z(H)
Bridge	DFB2-27-13-00Z(H)

Business data

Order number	30020000135
Packing unit	10 SKT
Minimum order quantity	10 SKT

Products weight (without packaging)	55g