
Áttekintés

Termék információ



DK-12/2-MC-21020000065

Heavy-duty insert,Number of contacts:12/2+PE,Dimension:16B,Rated voltage :690/250V,Rated current:40/10A ,Male insert,Crimping connector

A termék előnyei

☑Crimping connection technology, high wiring efficiency
☑Suitable for vibration occasions;
☑The wiring harness can be pre-installed;
☑Choose contacts with different wire diameters and coatings;
☑High-density pins, saving installation space;
☑With grounding protection。

Termék tanúsítás

CE

Műszaki adatok

Termékrajz

3D modell

Marking

classification	Insert
Series	DK

versions

Connection method	Crimping connection
Female/Male	Male
Dimension	16B
Number of positions	12/2

PE Contacts	Yes

Material characteristics

Material（insert）	Polycarbonate（PC）
Materia（Contact）	Copper alloy
Surface（Contact）	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White（RAL 7032）
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	690/250V
Rated pulse voltage	8/4KV
Pollution level	3
On the basis of UL /CSARated current	600/300V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3/3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	6-9mm
Conductor cross sections（mm²）	1.5-6.0mm²/0.14-2.5mm²
Conductor cross sections(AWG)	16-10/26-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984

Melléklet

Accessories

Crimping tool|Removal tool	/

Üzleti adatok

Rendelésszám	21020000065
Csomagolási egység	100
Minimális rendelési mennyiség	5
A termékek súlya (csomagolás nélkül)	65