## Panoramica

### Informazioni sul prodotto



# D16B-BK-4g-21010000275

16B Lower base,Four levers,no back cover

### Vantaggi del prodotto

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;
☑Various installation methods and outlet directions to meet on-site wiring requirements;
☑Snap-in combination structure, dustproof, waterproof, easy operation;

### Certificazione del prodotto

## Dati tecnici

### Disegno del prodotto

### Modello 3D

### Marking

| | |
|---|---|
| classification | Upper Housing/base |
| Series | B |
| Type | Hole mounting base |
| Specification | Low structure |

### versions

| | |
|---|---|
| Dimension | 16B |
| locking Category | Double lock |

### Material characteristics

| | |
|---|---|
| Flammability rating | V-0 |

| | |
|---|---|
| RoHS | conform |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey（RAL 7037） |
| Material (seal) | NBR |

Technical specification

| | |
|---|---|
| Limiting temperatures | -40℃~+125℃ |
| IP class | IP65 |

## Accessori

## Dati aziendali

| | |
|---|---|
| numero d'ordine | 21010000275 |
| Unità di imballaggio | 100 |
| Quantità di ordine minimo | 1 |
| Peso dei prodotti (senza imballaggio) | 85.5 |