
## 概要

### 製品情報



# STB4-QU-11100000026

Pull back rail terminal, wiring method: pull back spring connection, rated voltage: 800V, rated current: 24A, connection quantity: 4, number of digits: 1, wiring capacity: 0.14mm²-6mm², AWG: 28-12, width: 6.15mm, color: gray, installation method: NS35/7.5，NS35/15

### 製品の特長

☑ The proven pullback connection technology has excellent seismic performance
☑ Can be connected to rated wires with or without cold heads
☑ Dual channel bridging well, with 2-20 bridge connectors for flexible separation
☑ Clear front identification, easily recognizable marking area

### 製品認証

## 技術データ

### 製品チャート

### 3Dモデル

### Wiring data

| | |
|---|---|
| Strip length | 9~10mm |
| Conductor cross section solid AWG | 28~10 |

### Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |

### UL Electrical parameters

| | |
|---|---|
| Rated voltage (Use Group B) | 600V |

### IEC Electrical parameters

| | |
|---|---|
| Rated current (Ⅲ / 3) | 32A |
| Rated surge voltage | 8KV |

Environmental protection

| | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

Dimension

| | |
|---|---|
| End plate width | 1.5mm |
| width | 5.2mm |

Overview

| | |
|---|---|
| Connection type | Pull back spring connection |
| Number of rows | 1 |
| number of connections | 4 |
| Open-end side panels | Yes |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

アクセサリ

Marker

| | |
|---|---|
| Top marker bar | ZS6/ZB6 |
| Side marking strip | ZSF6/ZT6 |

Accessories

| | |
|---|---|
| A screwdriver | 0.6x3.5 |
| Bridge components | DFBSXXX-6.2(XXX:2,3,4,5,6,7,8,9,10,20) |
| End plate | D-STB4-QU |
| Grouping partition | ATP-DS / ATP-PC N |

## Installation

| | |
|---|---|
| Terminal fixing components | E-PC 1100A / E-WS N |
| Terminal strip marking bracket | DLM2 / KLM3-20x8 / KLM3-44x8 |
| DIN rail | NS35/7.5-1000-00A(H) |
| Guide rail protection cover | AP3-COVER / AP3-T / AP3-T-KS |

## ビジネスデータ

| | |
|---|---|
| 注文番号 | 11100000026 |
| パッキングユニット | 50 |
| 最小注文数量 | 50 |
| 1個あたりの重量（梱包を含めない） | 14.95 |