
概要

製品情報



STB1.5/1P-11100000004

Pull back rail terminal, wiring method: pull back spring connection, rated voltage: 500V, rated current: 13.5A, connection quantity: 2, number of digits: 1, plug removal: 1, wiring capacity: 0.14mm ² -1.5mm ², AWG: 24-14, width: 3.45mm, color: gray, installation method: NS35/7.5，NS35/15

製品の特長

☑ The proven pullback connection technology has excellent seismic performance
☑ Can be connected to rated wires with or without cold heads
☑ Dual channel bridging well, with 2-20 bridge connectors for flexible separation
☑ Clear front identification, easily recognizable marking area

製品認証

技術データ

製品チャート

3Dモデル

Wiring data

Strip length	9~10mm
Conductor cross section solid	0.2~1.5mm²
Conductor cross section flexible	0.2~1.5mm²
Conductor cross section solid AWG	24~14

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

UL Electrical parameters

Rated voltage (Use Group B)	300V

IEC Electrical parameters

Rated voltage (III / 3)	500V
Rated surge voltage	6KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

End plate width	1.5mm
length	50.6mm
width	3.5mm

Overview

Connection type	Pull back spring connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Marker

Top marker bar	ZS3.5/ZB3.5
Side marking strip	ZSF3.5/ZT3.5

Accessories

A screwdriver	0.6x3.5

Bridge components	DFBSXXX-3.5(XXX:2,3,4,5,6,7,3.5,9,3.5,20)
End plate	D-STB1.5
Grouping partition	ATP-DS / ATP-PC N

Installation

Terminal fixing components	E-PC 1100A / E-WS N
Terminal strip marking bracket	DLM2 / KLM3-20x8 / KLM3-44x8
DIN rail	NS35/7.5-1000-00A(H)
Guide rail protection cover	AP3-COVER / AP3-T / AP3-T-KS

ビジネスデータ

注文番号	11100000004
パッキングユニット	80
最小注文数量	80
1個あたりの重量（梱包を含めない）	4.45