概要

製品情報



DA-003-M-21020000002

Heavy-duty insert,Number of contacts:3+PE,Dimension:3A,Rated voltage:400/230V,Rated current:10A,Male insert,Screw connector

製品の特長

☑Screw connection technology, applicable to a wide range of wire specifications；
☑No need special tools,easy to operate；
☑Less materials, easy to manage；
☑With grounding protection。

製品認証

技術データ

製品チャート

3Dモデル

Marking

classification	Insert
Series	DA

Versions

Connection method	Screw connection
Female/Male	Male
Dimension	3A
Number of positions	3
PE Contacts	Yes

Material characteristics

Material（insert）	Polycarbonate（PC）
Materia（Contact）	Copper alloy
Surface（Contact）	Silver plated
Flammability rating	V-0
color	Grey/White（RAL 7032）
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	10A
	400/230V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	4.5mm
Rated torque	0.25N.m
Conductor cross sections（mm²）	0.75-1.5mm²
Conductor cross sections(AWG)	18-16AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984

アクセサリ

Accessories

Screwdriver	/

ビジネスデータ

注文番号	21020000002
パッキングユニット	100
最小注文数量	5
1個あたりの重量（梱包を含めない）	13.65