概要

## 製品情報



# PM-M12B-05P-MM-SR8A01-20030000813

Sensor/Actuator Cable,PVC,black,UL2517,Male plug,acodado M12,Coding B,Unshielded,Trimming cable end,Cable Cable length:1m

## 製品の特長

☑Sealing optimization, protection level up to IP68
☑Meet the harsh environment
☑Suitable for various occasions connection technology
☑Compatible with the international and domestic same series products

## 製品認証

RoHS REACH

技術データ

## 製品チャート

## 3Dモデル

## Environmental conditions

| | |
|---|---|
| Ambient temperature | -25℃...85℃ |
| IP class | IP68 |

## General parameters

| | |
|---|---|
| Rated current | 4A |
| | 60V |
| Number of potentials | 5 |
| Insulation resistance | ≥ 100 MΩ |
| Error-proof coding | B-Code |

| | |
|---|---|
| Overvoltage level | II |
| Pollution level | 3 |
| Insertion and pullout cycle | ≥ 100 |
| Torque | 0.4 Nm |

Material

| | |
|---|---|
| Flammability rating ,in line with UL94 | V0 |
| Flammability rating ,in line with UL97 | HB |
| Contact material | CuZn |
| Material contact surface | Au |
| Contact carrier material | PU |
| Fixture body material | TPU |
| Coil material | Zinc alloy, nickel plated |
| Sealing material | Silicon |

Standards and specifications

| | |
|---|---|
| Standards/specifications | IEC 61076-2-101 |

Cable

| | |
|---|---|
| Cable type | PVC Black |
| Cable type(abbreviation) | PVC |
| UL AWM form | UL2517 |
| Cross section | 0.34mm² |
| AWG signal wire | 22AWG |
| Wire structure Signal wire | 17/0.16mm² |
| Core diameter (including insulation layer) | 1.30±0.05mm |
| Wire color | 1 Brown 2 White 3 Blue 4 Black 5 Gray |
| Thickness, insulation | 0.6mm |

| | |
|---|---|
| Cable outer diameter D | 5.4 ±0.2mm |
| Outer sheath, material | PVC |
| Conductor insulation material | PVC |
| Conductor material | Tinned copper |
| Insulation resistance | ≥100MΩ |
| Conductor resistance | Maximum 59.4Ω/km (at 20 °C) ) |
| Nominal cable voltage | 300V |
| Cable test voltage | 2000V |
| Flame retardant | Comply with UL 758/1581 FT1 standard |
| Halogen free | Yes |

Dimension

| | |
|---|---|
| Cable length | 1m |

## アクセサリ

Accessories

| | |
|---|---|
| Sealing cap | CAP-M12-FP-8001 |

## ビジネスデータ

| | |
|---|---|
| 注文番号 | 20030000813 |
| パッキングユニット | / |
| 最小注文数量 | 100 |
| 1個あたりの重量（梱包を含めない） | / |