概要

製品情報



WSF4-TA-08A(H)-11030000564

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 24 V, Rated current: 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 4 mm², AWG: 28 - 12, Width: 6 mm, Fuse type: Glass / ceramics / ..., Fuse type: G / 5 x 20, Color: black, Suitable for 24 V DC LED, Mounting type: NS 35/7.5, NS 35/15.

製品の特長

☑WS Fuse wire terminal；
☑spring-cage connection technology, good anti-vibration performance；
☑Use an ordinary flat-blade screwdriver, you can easily wire and take the wire；
☑Unique plug-in bridge, high circuit connection efficiency；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

製品認証

CE

技術データ

製品チャート

3Dモデル

Wiring data

Strip length	10~12mm
Conductor cross section solid	0.2~4mm²
Conductor cross section flexible	0.2~4mm²
Conductor cross section solid AWG	28~12

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）

Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated current (Ⅲ / 3)	6.3A

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	68mm
NS 35/15 Height	75.5mm
length	60mm
width	6mm
Height	66.6mm

Overview

Connection type	Pull back spring connection
Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
fuse	G/5 x 20
Fuse type	Glass/ceramic/...

アクセサリ

Marker

Top marker	ZB6

Side marker	/
Marker support	/
Warning cover	EEA4

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.5×3.5
Adjacent jumper (2P)	WFA4
Alternate jumper (2P)	WFB4
Staggered jumper (2P)	/
End cover	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号	11030000564
パッキングユニット	115
最小注文数量	115
1個あたりの重量（梱包を含めない）	13.69