概要

製品情報



SD-M12A-05P-MM-SH8001-20030001108

Sensor/Actuator Female socket,M12,Coding A,Front panel installation/PG9 Thread mounted,Soldering cup

製品の特長

☑Sealing optimization, protection level up to IP68
☑Meet the harsh environment
☑Suitable for various occasions connection technology
☑Compatible with the international and domestic same series products

製品認証

技術データ

製品チャート

3Dモデル

Environmental conditions

Ambient temperature	-40℃...105℃
IP class	IP68

General parameters

Rated current	4A
	60V
Number of potentials	5
Insulation resistance	≥ 100 MΩ
Error-proof coding	A-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Installation in front of the board

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101

アクセサリ

Accessories

Sealing cap	CAP-M12-FP-8002

ビジネスデータ

注文番号	20030001108
パッキングユニット	/
最小注文数量	100
1個あたりの重量（梱包を含めない）	/