
概要

製品情報



15EDGVC-THR-2.5 Reel package-10030000843

Pluggable terminal blocks,Rated current:5A.Rated voltage（Ⅲ/2）:250V,pitch:2.5mm,Color:black,Contact surface :Tin

製品の特長

☑ Suitable for SMT welding process
☑ The plug direction is perpendicular to PCB，Can meet the needs of different connectors

製品認証

技術データ

製品チャート

3Dモデル

Processing notes

Process	Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	150V
Rated current (B)	4A

Electrical parameters IEC

Rated voltage	250V
Rated current	5A
Rated voltage(Ⅲ/2)	250V
Rated surge voltage(Ⅲ/2)	2.5KV

Item properties	
Connection direction	90°
Type of installation	PCB Soldering
Pitch	2.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1
Material data	
Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40℃~130℃

アクセサリ

Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	/

Bridge	/
Marking strip	/
Others	/

ビジネスデータ

注文番号	10030000843
パッキングユニット	220
最小注文数量	30
1個あたりの重量（梱包を含めない）	0.78