概要

製品情報



MDR cable-DX220-1DS-500-00A(H)-23040000067

MDR cable,connector1:MDR slot connector（1×50 Core,180° output）,connector2:multi-Core Cable

製品の特長

☑The cable is soft and has good bending resistance
☑Prefabricated connector, beautiful appearance
☑ Provide single-ended and double-ended cables
☑ Suitable for servo position control mode
☑ Save wiring time, and can achieve fast wiring with the company's interface module

製品認証

技術データ

製品チャート

3Dモデル

Environmental data

Ambient temperature (operation)	-20 °C ... 80 °C
Ambient temperature (storage / transport)	-20 °C ... 80 °C

Standards/Regulations

Flame retardant	ULVW-1
Oil resistance	Oil resistant
Gasoline resistance	≤246Ω/KM
Connection meets standards	UL758

Technical data

Maximum allowable working voltage	30VDC
Maximum current carrying capacity of each path	0.7A
cable length	0.5米
Cable outer diameter	6.5mm
Single strand, cross-sectional area	0.08mm²
Single strand, cross section (AWG)	28

Connection data 1

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	50
spacing	1.27mm
Exit angle	180°

Connection data 2

Connection name	On-site side
Connection method	Multi-core wire
Connection volume	1
Number of digits	50
spacing	1.27mm

Overview

Single wire, number of twisted wires	50
Single stranded wire, material	Tinned copper
shield	Yes
Outer sheath, material	PVC
Outer sheath,color	black

アクセサリ

ビジネスデータ

注文番号	23040000067
パッキングユニット	1
最小注文数量	10
1個あたりの重量（梱包を含めない）	50