## 概要

### 製品情報



# D16A-SF-1L-CV-2PG16-21010000255

16A Lower base,single buckle,back cover ,side entry,double PG16 Thread hole,Wear protective cover

### 製品の特長

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock；
☑Various installation methods and outlet directions to meet on-site wiring requirements；
☑Snap-in combination structure, dustproof, waterproof, easy operation；

### 製品認証

## 技術データ

### 製品チャート

### 3Dモデル

### Marking

| | |
|---|---|
| classification | Upper Housing/base |
| Series | A |
| Type | Surface mount base |
| Description | With plastic dust cover |
| Specification | Low structure |

### Versions

| | |
|---|---|
| Dimension | 16A |
| locking Category | Single lock |
| Thread specification | 2x PG16 |

### Material characteristics

| | |
|---|---|
| Flammability rating | V-0 |
| RoHS | conform |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey（RAL 7037） |
| Material (seal) | NBR |
| Material (lock catch) | Zinc plated |

Technical specification

| | |
|---|---|
| Limiting temperatures | -40℃~+125℃ |
| IP class | IP65 |

アクセサリ

ビジネスデータ

| | |
|---|---|
| 注文番号 | 21010000255 |
| パッキングユニット | 100 |
| 最小注文数量 | 1 |
| 1個あたりの重量（梱包を含めない） | 226.5 |