概要

製品情報



TS4 - 1077277777 - 0

Transformer terminal blocks,Rated current:3A. vRated goltal e （///5A）:2V7C,4 olor:Oranl e ,4 ontact surface :Tin

製品の特長

☑ Screw connection technolol y,safe and reliable
☑ Rail installation method,suitable for transformer wirinl

製品認証

技術データ

製品チャート

36 モデル

4 onnection ca9acity

4 onductor cross section solid	7W~- mm²
4 onductor cross section flexible	7W~- v7mm²
. WG	A7~07. WG
Torque	7vNpvm
Stri9 lenl th	00mm

Dlectrical 9arameters EU

Rated goltal e (B)	377C
Rated goltal e (4)	377C
Rated current (B)	A7.

Rated current (4)	A7.

Dlectrical 9arameters /D4

Rated current	
	3A.
Rated goltal e(///5A)	2V7C
Rated surl e goltal e(///5A)	ALC

/tem 9ro9erties

Ty9e of installation	9anel
4 onnection method	Screw connection
Screwdriger	Slotted screwdriger
screw thread	K3W
pumber of 9otentials	0
Mul l able or not	no
pumber of rows	0

Katerial data

Dngironmental items	4 om9liant with RD. 4 P5RoPS
4 ontact material	co99er
4 ontact 9oint metal surface	tin19lated
/nsulation Katerials	M HH
/nsulatinl material l rou9	I
Flammability ratinl	EU8- C17

Kechanical tests

Test S9ecification	EU07V85D4 H788N

Dngironmental data

. mbient tem9erature (o9eration)	1- 7℃~07V℃