## Panoramica

### Informazioni sul prodotto



# D48B-TE-2g-M40-21010000420

48BHoods,double levers,top entry,M40 Thread hole

### Vantaggi del prodotto

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;
☑Various installation methods and outlet directions to meet on-site wiring requirements;
☑Snap-in combination structure, dustproof, waterproof, easy operation;

### Certificazione del prodotto

## Dati tecnici

### Disegno del prodotto

### Modello 3D

### Marking

| | |
|---|---|
| classification | Upper Housing/base |
| Series | B |
| Type | Top housing |
| Specification | High structure |

### versions

| | |
|---|---|
| Dimension | 48B |
| locking Category | Single lock |
| Wiring method | Top entry |
| Thread specification | 1x M40 |

### Material characteristics

| | |
|---|---|
| RoHS | conform |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey（RAL 7037） |

Technical specification

| | |
|---|---|
| Limiting temperatures | -40℃~+125℃ |
| IP class | IP65 |

## Accessori

## Dati aziendali

| | |
|---|---|
| numero d'ordine | 21010000420 |
| Unità di imballaggio | 100 |
| Quantità di ordine minimo | 1 |
| Peso dei prodotti (senza imballaggio) | 750 |