DEGSON

## 概要

### 製品情報



# 15EDGVC-THR-2.5-10030004106

Pluggable terminal blocks,Rated current:5A.Rated voltage（Ⅲ/2）:250V,pitch:2.5mm,Color:black,Contact surface :Tin

### 製品の特長

☑ Suitable for SMT welding process
☑ The plug direction is perpendicular to PCB，Can meet the needs of different connectors

### 製品認証

## 技術データ

### 製品チャート

### 3Dモデル

### Processing notes

| | |
|---|---|
| Process | Wave soldering/manual soldering |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 150V |
| Rated current (B) | 4A |

### Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 250V |
| Rated current | 5A |
| Rated voltage(Ⅲ/2) | 250V |
| Rated surge voltage(Ⅲ/2) | 2.5KV |

| Item properties | |
|---|---|
| Connection direction | 90° |
| Type of installation | PCB Soldering |
| Pitch | 2.5mm |
| Number of potentials | 4 |
| Pluggable or not | Yes |
| Number of rows | 1 |
| **Material data** | |
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact point metal surface | tin-plated |
| Insulation Materials | High temperature resistant materials |
| Insulating material group | IIIa |
| Flammability rating | UL94V-0 |
| **Mechanical tests** | |
| Test Specification | IEC61984/ UL1059 |
| **Environmental data** | |
| Ambient temperature (operation) | -40℃~130℃ |

アクセサリ

| Tool | |
|---|---|
| Screwdriver | / |
| Operating tool | / |
| **Accessories** | |
| Coding strip | / |

| | |
|---|---|
| Bridge | / |
| Marking strip | / |
| Others | / |

## ビジネスデータ

| | |
|---|---|
| 注文番号 | 10030004106 |
| パッキングユニット | 3500 |
| 最小注文数量 | 30 |
| 1個あたりの重量（梱包を含めない） | 1.16 |