
概要

製品情報



WS16-SD-11030000086

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 800 V, Rated current: 76 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 16 mm², AWG: 24 - 6, Width: 12 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

製品の特長

☑spring-cage connection technology, good anti-vibration performance；
☑Use an ordinary flat-blade screwdriver, you can easily wire and take the wire；
☑Unique plug-in bridge, high circuit connection efficiency；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

製品認証

CE

技術データ

製品チャート

3Dモデル

Wiring data

Strip length	16~17mm
Conductor cross section solid	0.2~16mm²
Conductor cross section flexible	0.2~16mm²
Conductor cross section solid AWG	24~6

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

UL Electrical parameters	
Rated current	65A

IEC Electrical parameters	
Rated voltage (III / 3)	800V
Rated current (III / 3)	76A
Rated surge voltage	8KV

Environmental protection	
REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension	
NS 35/7,5 Height	52.6mm
End plate width	4mm
NS 35/15 Height	60.1mm
length	58.5mm
width	12mm
Height	49.85mm

Overview	
Connection type	Pull back spring connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Marker

Top marker	/
Side marker	ZT12 / WB5
Marker support	/
Warning cover	EEA16

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.8×5.5
Adjacent jumper (2P)	WFA16
Alternate jumper (2P)	WFB16
Staggered jumper (2P)	/
End cover	D-WS16-SD

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

Accessories

End cover	D-WS16-SD
Bridge	WFA16
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号	11030000086
パッキングユニット	50
最小注文数量	50
1個あたりの重量（梱包を含めない）	27.86